





Energizer® EVEREADY® RAYOVAC®

Bright and dependable, the READYFLEX Floating Lantern is a great choice for everyday needs. Featuring long lasting LED technology, this ergonomic solution also shines up to 5X brighter than standard LED technology. With READYFLEX technology, users also receive the flexibility to operate with either 2 or 4 batteries. Users can be ready for everyday or emergency situations with just 2 D batteries, or they can extend runtime for days on 4 D batteries. With hours and hours of clear, uniform light, users will be prepared for a wide variety of outdoor and indoor tasks.

| Lumens | Runtime | Beam Distance | Water Ingress |
|--|--|---|---|
|  80 LUMENS |  70h |  175m |  IPX4 |



BATTERY SPECIFICATIONS

| | |
|------------------------|-----------------------|
| Battery Type | EVR SHD CZ, ROV CZ HD |
| Battery Size | D |
| Number of Cells | 4 (2) |

BATTERY PERFORMANCE

| Modes | Lumens (lm) | Runtime (h) | Beam Distance (m) |
|----------|-------------|-------------|-------------------|
| On, 4 CZ | 80 | 140 | 175 |
| On, 2 CZ | 80 | 70 | 175 |

BATTERY SPECIFICATIONS

| | |
|------------------------|-------------------------------|
| Battery Type | ENR Alkaline, ROV Alkaline HE |
| Battery Size | D |
| Number of Cells | 4 (2) |

BATTERY PERFORMANCE

| Modes | Lumens (lm) | Runtime (h) | Beam Distance (m) |
|-----------|-------------|-------------|-------------------|
| On, 4 Alk | 65 | 400 | 150 |
| On, 2 Alk | 65 | 200 | 150 |

DESIGN BENEFITS

- ✓ Floats for easy retrieval
- ✓ READYFLEX technology enables operation on 2 or 4 D cell batteries
- ✓ Non-slip grip

PERFORMANCE BENEFITS

- ✓ Powerful beam
- ✓ Up to 5X brighter than standard LED technology
- ✓ Long run time

LIGHT AND POWER SOURCE

- ✓ Features LED Technology
- ✓ Operates on either 2 or 4 D batteries
- ✓ CCT 5000 CRI 70

PRODUCT SPECIFICATIONS

| | |
|--------------------|--|
| Weight: | 250 Grams / 8.8 Ounces |
| Dimensions: | 177 mm x 125 mm x 125 mm 7" x 5" x 5" |

ELECTRICAL CHARACTERISTICS

| | |
|-----------------------------------|----------------------|
| Nominal Power Consumption: | 0.46 W |
| Batteries: | 4 D Eveready 6.0V dc |
| LED Specifications: | LED 3.0V/155 mA |

DISCLAIMERS

Tested according to ANSI FL1 Standards.

CERTIFICATES AND COMPLIANCE

EMC, EN62471



BATTERY SPECIFICATIONS

| | |
|------------------------|------------|
| Battery Type | EVR SHD CZ |
| Battery Size | AA |
| Number of Cells | 4 (2) |

| Modes | Lumens (lm) | Runtime (h) | Beam Distance (m) |
|----------|-------------|-------------|-------------------|
| On, 4 CZ | 70 | 23 | 175 |
| On, 2 CZ | 60 | 16 | 160 |

Publish Date: 10-16-2020

OPERATING INSTRUCTIONS

1. Press on/off button to turn on.

BATTERY CHANGING INSTRUCTIONS

1. Batteries (4X D) are user replaceable.
2. Unscrew head of flashlight and insert batteries according to instruction on the inside of the flashlight.