PRODUCT DATASHEET

NiMH Battery Charger (CHFC3)

Download Instructions (Americas) Download Instructions (Rest of World)

Universal Charger



• Helps batteries retain capacity by preventing damagé fróm overcharge



ENSURES FULL CHARGE

• Charges batteries to 100% capacity




EASY TO USE

• LED lights indicate when batteries are charging



VERSATILE

Charges AA, AA, C, D and 9V NiMH batteries





LED Functions/Status

When AAA/AA batteries are placed in the charger LED Functions:

Green LED on:

Charge completed, or no battery inserted Green LED off: Green LED flashing: Alkaline protection or short circuit protection

Product Detail:

Designation: Universal Charger

Model: CHFC3 Color: Black

Charging Capability: AA/AAA/C/D/9V

Charging Times: (estimated)

| Battery | Capacity | Estimated |
|---------|-----------|-----------|
| (NiMH) | (mAh) | (time) |
| AA | 1300-2000 | 3-4 hrs |
| AA | 2000-2300 | 4-5 hrs |
| AAA | 500-800 | 2-3 hrs |
| C/D | 2500 | 5 hrs |
| 9V | 175 | 8 hrs |
| | | |

Shutoff Mechanism: Delta V Detection: 5mV per cell for "AA-AAA-C-D"

Timer Control: 2 or 4 "AA-C-D": 5 hrs 2 or 4 "AAA": 3.5 hrs

1 or 2 "9V": 8 hrs

Charging Current: "AA-C-D" 650mA

"AAA" 400mA "9V" 30mA

Trickle Charge: None

Input Rating: 100-240VAC, 50-60Hz, 6W

Typical Weight 322 grams

Dimensions (mm): 48 x 199 x 107 (H x L x W)

Safety Features: Short Circuit and Reverse Polarity Protection

Primary Battery Detection **Bad Battery Detection** Delta V Charging Cut Off

Safety Timer to Prevent Overcharge

Before Using Your Charger:

Please read all instructions and cautionary markings on the battery charger, batteries, and device.

Best used with *Energizer*_® NiMH batteries.

Important Notice

This datasheet contains information specific to products manufactured at the time of its publication.

Contents herein do not constitute a warranty.