Article Data Sheet

VARTA Indestructible L30 Pro 6AA w/o Batt.





Extremely robust (4m drop test, IP67) LED Lantern with four light levels and night mode, impact resistance IK08, removable head and integrated base hook for hanging option.



Information

- Extremely robust (4m drop test) camping lantern with shock-absorbing rubber elements
- impact resistance rating IK08 (IEC 62262)
- 4m drop test
- Water and dust proof (IP67)
- 4 light lmodes: high, med, low, Nightlight mode
- Nightlight mode to be activated by double click
- 360° light distribution
- Removable head and a hook integrated into the base allow for hanging up the lantern
- Extra-wide handle, which can be folded down into the casing on either side for protection, fits perfectly in the hand
- Designed for maximum durability
- Operated with 6AA batteries (excl)

Article Details

Ordernumber
Customs Tariff Number
Country Of Origin
Beam Range
Runtime
Total light output
Product Diameter mm
Product Length / Depth mm
Product Width mm
Product Weight g

18761 101 111 85131000 China (up to) 20.00 m (up to) 360 h (up to) 450 lm 98.30 215.00 107.20 623.00

Logistical Data	Content (SU)	GTIN / EAN	Facing (mm)	Depth (mm)	Height (mm)	Weight (kg)
VBE (stufe_VBE)	1	40 08496 987146	122.00	102.00	340.00	0.64
SK2 (stufe_SK2)						
SK1 (stufe_SK1)						
VSK (stufe_VSK)	4	40 08496 987153	240.00	240.00	258.00	2.89
PAL (stufe_PAL)	180	40 08496 075980	800.00	1,200.00	924.00	150.88
Layer / Pallet	Master carton / Layer		Master carton / Pallet		Minimum pieces / shipment unit	
3	15		45		4	

All mentioned products and specifications are subject to change. In case of non-availability of any product or item, VARTA Consumer Batteries GmbH & Co. KGaA cannot be held responsible. Some of the products shown may not be available in all countries. The pictures might be different to the original products. Technical changes and errors reserved.



VARTA Consumer Batteries GmbH & Co. KGaA | Alfred-Krupp-Str. 9 | 73479 Ellwangen | Germany P.O. Box 1363 | 73473 Ellwangen | Germany | Phone (+49) 7961 83 0 | Fax (+49) 7961 83 440